




SELF TAPPING SCREWS

SQUARE DRIVE PAN HEAD Self Tapping Screws



This type of recess has a square center opening, slightly tapered side walls and a conical bottom.

Nominal Size or Basic Screw Diameter		H		R	M		T		Driver Size	P	
		Head Height		Head Radius	Recess Square		Recess Depth			Penetration Gauging Depth	
		Max	Min	Min	Max	Min	Max	Min		Max	Min
3	0.0990	0.078	0.067	0.010	0.071	0.0696	0.073	0.063	0	0.038	0.032
4	0.1120	0.086	0.075	0.010	0.071	0.0696	0.073	0.063	0	0.038	0.032
5	0.1250	0.095	0.083	0.015	0.091	0.090	0.113	0.105	1	0.065	0.057
6	0.1380	0.103	0.091	0.015	0.091	0.090	0.113	0.105	1	0.065	0.057
7	0.1510	0.111	0.099	0.015	0.091	0.090	0.113	0.105	1	0.065	0.057
8	0.1640	0.120	0.107	0.015	0.112	0.111	0.140	0.119	2	0.075	0.065
10	0.1900	0.137	0.123	0.020	0.112	0.111	0.140	0.119	2	0.075	0.065
12	0.2160	0.153	0.139	0.025	0.133	0.1315	0.165	0.155	3	0.095	0.085
1/4	0.2500	0.175	0.160	0.035	0.133	0.1315	0.165	0.155	3	0.095	0.085
5/16	0.3125	0.216	0.198	0.040	0.191	0.1895	0.201	0.191	4	0.100	0.090
3/8	0.3750	0.256	0.237	0.040	0.191	0.1895	0.201	0.191	4	0.100	0.090